

# Jazzy<sup>®</sup> 623

With features like standard 4-pole motors, Mid-Wheel 6<sup>®</sup> drive design and ATX Suspension, the Jazzy<sup>®</sup> 623 is engineered to meet the needs of the most active user. The Jazzy 623 comes standard with high-back seat and Dynamic Shark controller to deliver exceptional performance capability at an excellent value.



**Pride<sup>®</sup>**  
Mobility Products  
Australia Pty. Ltd.

— LIVE YOUR BEST —

## SPECIFICATIONS

<b>Weight capacity</b>	136 kg (300 lbs.)
<b>Maximum speed<sup>1</sup></b>	Up to 8 km/h (5 mph)
<b>Ground clearance<sup>2</sup></b>	6.35 cm (2.5") at front castor 7.62 cm (3") at rear castor
<b>Turning radius<sup>2,6</sup></b>	50.8 cm (20") <sup>7</sup>
<b>Overall length<sup>2,6</sup></b>	90.17 cm (35.5") <sup>7</sup>
<b>Overall width<sup>2,6</sup></b>	61 cm (24")
<b>Drive wheels</b>	35.56 cm (14") (pneumatic)
<b>Front castors</b>	15.25 cm (6") solid OMNI-casters
<b>Rear castors</b>	15.25 cm (6") solid OMNI-casters
<b>Suspension</b>	Active-Trac <sup>®</sup> ATX Suspension
<b>Drivetrain</b>	Two-motor, Mid-Wheel 6 <sup>®</sup>
<b>Braking system</b>	Intelligent braking (electronic, regenerative disc brakes)
<b>Standard electronics</b>	75 amp, Dynamic Shark controller
<b>Standard seat</b>	high-back seat
<b>Specialty controls</b>	Yes
<b>Battery charger</b>	Off-board, 8 amp
<b>Per-charge range<sup>1,4</sup></b>	Up to 25.6 km (15.9 miles)
<b>Battery requirements<sup>3</sup></b>	(2) 12 volt deep-cycle
<b>Battery size (largest)</b>	55 AH
<b>Battery weight<sup>5</sup></b>	17.7 kg (39 lbs.) each
<b>Base weight</b>	62 kg (137.5 lbs.) (without batteries)
<b>Standard seat weight</b>	20 kg (44 lbs.) (high-back)
<b>Std. seating dimensions</b>	45.7 cm x 45.7 cm (18" x 18")

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.



07 3265 4663

2/452 Bilsen Rd, Geebung QLD 4034  
sales@powermobility.com.au • powermobility.com.au

20-24 Apollo Drive Hallam, Victoria 3803

ACN 088 609 661 ABN 66 088 609 661

(Tel) (03) 8770 9600 • (Fax) (03) 9703 2720 • www.pridemobility.com.au

## FEATURES

- Mid-Wheel 6<sup>®</sup> allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance<sup>®</sup> Power Positioning
- Low impact OMNI-Casters (nylon, spherical-shaped castors) on front and rear prevent wheel hang-ups
- ATX Suspension (Active-Trac<sup>®</sup> with extra stability) incorporates front OMNI-Casters and semi-independent rear castor beam for enhanced performance over more varied terrain

## OPTIONS

- Solid tyres
- Cane/crutch holder
- Cup holder
- Walker holder
- Swing-away footrests
- Contoured high-back seat
- Swing-away joystick
- Synergy<sup>®</sup> Seat
- Elevating leg rests
- Specialty Seat
- Oxygen tank holder
- TRU-Comfort seating
- Quantum dealers only: TB2 Tilt and Synergy<sup>®</sup> Seat

## COLOUR



Candy  
Apple Red



Viper  
Blue

- 1) Varies with base model, user weight, terrain type, battery amp hour rating (AH), battery charge, battery condition, motors, controller type, tyre type, and tyre condition. This specification is subject to a variance of +10%, -5%.
- 2) Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3) AGM or gel cell type required.
- 4) Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5) Battery weight may vary based on manufacturer.
- 6) Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.
- 7) Without foot riggings.



Quality  
Endorsed  
Company

9001 QEC20029  
SAI Global

**PRIDE**<sup>®</sup>  
PERFORMANCE MOBILITY

— LIVE YOUR BEST<sup>®</sup> —