4-Wheel Stability with 3-Wheel Manoeuvrability



Patented, intelligent-turning







Exclusive iTurn Technology®



Full LED lighting package

Get a 4-wheel scooter with a 3-wheel turning radius with the **Pride® Zero Turn Scooter** and Pride's patented, intelligent-turning technology™. Navigate tight corners and small spaces effortlessly with a 97.2 cm (38.25") turning radius. Illuminate your ride with bright LED lighting, while the Zero Turn's dual motors and CTS Suspension ensure a smooth and comfortable drive.

Pride Zero Turn Scooter **Specifications**

Weight Capacity	147 kgs (350 lbs.)
Maximum Speed ¹	Up to 6.4 km/h (4 mph)
Ground Clearance ²	3.3 cm (1.3") at motor
Turning Radius ²	97.2 cm (38.25")
Overall Length ²	116.2 cm (45.75")
Overall Width ²	50.8 cm (20")
Front Tyres	5 x 17.8 cm (2" x 7") solid
Rear Tyres	6.35 x 22.9 cm (2.5" x 9") solid
Range Per Charge ^{2,4}	Up to 16 km (10 miles)
Total Weight Without Batteries	54 kg (120 lbs.)
Heaviest Piece When Disassembled	21.8 kg (48 lbs.) (rear section)
Standard Seating	Type: Foldable, molded plastic Weight: 12 kg (27 lbs.) Material: Black vinyl Dimensions: Width: 43.2 cm (17") Depth: 43.2 cm (17")
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Electronic, regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12V deep-cycle Size: (2) 22 AH Weight : Battery box (15 kg) (32 lbs.) Each (6 kg)
Battery Charger	Off-board, 3.5 amp
Delta Tiller	Yes
Colour Options	







- The inclusion of iTurn Technology®
- First ever indoor 4-wheel scooter
- USB charging port built into the tiller
- Contemporary new rim design
- CTS Suspension for comfortable long range use
- Delta tiller, ergonomic wraparound
- Dual motors for added traction in rough
- Feather-touch disassembly
- Front basket
- Full LED lighting package
- Under seat storage (standard)
- Your choice of three interchangeable shrouds

Accessories

- · Pride rear bag/walking stick holder
- Walker holder*
- · Oxygen tank holder*
- Mobile phone holder
- Cup holder
- Rear view mirror
- Saddle bag

*Must have Pride rear bag to attach

- $Varies\ with\ user\ weight, terrain\ type, battery\ amp-hour\ (AH), battery$ charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
 Dueto manufacturing tolerances and continual product improvement,
- this specification can be subject to a variance of (+ or 3%).

 AGM or gel cell type required.
- Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO
 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

