



<25 km
Range per Charge



159 kg
Weight Capacity



125 cm
Turning Radius



Get Amongst It!

The Pride Outback® 4x4 Powerchair is your ultimate adventure companion, ready to tackle almost any terrain with confidence. Designed for superior performance, this rugged powerchair features powerful 4-pole sealed motors and all-wheel drive for unbeatable traction and stability. Its robust construction ensures a smooth and comfortable ride on uneven surfaces, featuring advanced (SRS) suspension and off-road pneumatic 14" knobby tyres. Whether you're navigating gravel paths, bush tracks, or country properties, the Outback® 4x4 Powerchair makes it a breeze.





Automotive-Grade (SRS) Suspension



LED Lighting Package



Centre Mount Foot Board (standard) or Swing Away Leg Rests (optional extra)

RANGE PER CHARGE (MAX) ¹	Up to 25.75 km at 136 kg Up to 27.4 km at 99.8 kg
MAXIMUM WEIGHT CAPACITY	159 kg
TURNING RADIUS	125 cm
MAXIMUM SPEED ¹	10 km/h
LENGTH & WIDTH ²	L: 106.7 cm W: 73.2 cm
WEIGHT OF HEAVIEST PIECE	76.5 kg
GROUND CLEARANCE	10.7 cm at motors
SEAT SIZE WIDTH & DEPTH (STANDARD)	W 46.5 cm x D 46.5 cm (18" x 18")
STANDARD SEAT WEIGHT	24.8 kg
HIGH-BACK SEAT-TO-FLOOR RANGE	52 cm - 55.5 cm
SPECIALTY SEATING OPTIONS	Q Captain Back, Flex

STANDARD ELECTRONICS	120A, Q-Logic 3e
SPECIALTY CONTROLS	Yes
DRIVE TRAIN	4 Motor, independent drive
BRAKING SYSTEM	Regenerative & electro-mechanical
SUSPENSION TYPE	Automotive-grade, smooth ride suspension (SRS)
DRIVE WHEELS	14" knobby pneumatic
BATTERY REQUIREMENTS ³	(2) 95Ah, 12V
BATTERY CHARGER	Off-board, 8A
BATTERY WEIGHT	26.6 kg each
COLOUR OPTIONS	 Sage  Tan

1. Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
2. Width of base (not including seat).
3. Deep cycle (AGM or gel cell type recommended)

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.